

BS 8417 Preservation of Wood Code of Practice



This is a very important standard for timber treatment which combines a number of European Standards (BSEN350) which collectively deal with wood durability, species and performance of preservatives.

BS8417 is a code of practice and advises on the choice of timber species and the use and application of wood preservatives depending on the end use.

BS8417 as a code of practice puts the emphasis for the responsibility for achieving the required penetration and retention of the timber preservative treatments with the timber treater.

If specifying particular preservative types or timber species, it is important to note that not all preservatives are appropriate for all Use Classes and that some timber species are not sufficiently permeable to achieve the penetration levels required, at least without additional preparation such as mechanical incising

When deciding on a timber species and end use the specifier needs to consider.

1. The natural durability of the chosen species
2. How the timber component will be used
3. The relevant treatment required to protect the species from rot and insect attack in that end use
4. The treatability of the chosen species

It should be noted that the treatability of timber varies between species. If a specific wood species is to be specified, care should be taken to ensure that a species chosen is appropriate to the treatment requirements. e.g. European whitewood is slightly durable but cannot be treated to hazard class 4 for use in ground contact.

Treatability. Refers to how easily timbers can be penetrated with vacuum pressure preservative treatments. The four levels of treatability in BSEN 350-2 are 'easy', 'moderately easy', 'difficult', 'extremely difficult' and any specifier should cross reference their chosen species with this standard.

Brookridge Timber takes great care in only using the correct species which will treat to the required hazard class and the treatment process is fully audited by Koppers the treatment solution provider. Additionally all of the company processes is audited by a 3rd party and Brookridge Timber has achieved ISO 9001 and the treatment process is also covered by this.